

Limit Switch Ordering Code Options

Series	Switch	Qty Switches	Conduit Entry		Color		Bracket	Certificates	
DXLW Weatherproof		1	4R	½" NPT	B	Black		U	CU _L , UL _L
DNLF Explosion Proof		2	6R	¾" NPT	Y	Yellow		C	CE
			3M	M20X1.5				A	ATEX
			4R	standard for DXLW				CM	CMRI
			6R	standard for DNLF				CC	CMRI CCOE

CODE	MAKE	TYPE	RATING
1A	Honeywell	SPDT Mech, AC/DC, 10A	10 Amp, 125 or 250 VAC, 50Hz, 60Hz, 220 VDC, NO/NC
11A	Honeywell	SPDT Mech, AC/DC, 15A	15 Amp, 125 or 250 VAC, 50Hz, 60Hz, 220 VDC, NO/NC
1B	Cherry	SPDT Mech, AC/DC, 5A	5 Amp, 125 or 250 VAC, 220 VDC, NO/NC
11B	Cherry	SPDT Mech, AC/DC, 15A	15 Amp, 125 or 250 VAC, 220 VDC, NO/NC
2A	P & F	Prox – IS, DC, 8mA Requires Power	8 VDC NC
12A	P & F	Prox – IS, DC, 100mA Requires Power	8 V, 24 V, 100mA, NO
22A	P & F	Prox – Non IS, DC, 100mA, LED	6 V - 24 V, 100mA, NO
32A	P & F	Prox – Non IS, DC, 100mA	8 V - 24 V, 100mA, NO
42A	P & F	Prox – Non IS, AC, 200mA	220 VAC, 200 mA, 50Hz/60Hz, NO
2C	lfm	Prox – IS, DC, 8 mA Requires Power	8 VDC, NO/NC
12C	lfm	Prox – Non IS, DC, 150mA, LED	24 VDC, 150 mA, NO/NC
3A	P & F	Prox – IS, DC, 3 mA Requires Power	8 VDC, 3mA, NC
13A	P & F	Prox – Non IS, DC, 100mA	10-60 VDC, 100mA, NO
3C	lfm	Prox – Non IS, DC, 200mA	24 VDC, 200mA, NO/NC
13C	lfm	Prox – IS, DC, 8mA	8 VDC, NO/NC
23C	lfm	Prox – Non IS, AC/DC, 100 mA	20-250 VAC/VDC
5A	Honeywell	DPDT Mech, AC/DC, 10A	10 Amp, 125 or 250 VAC, 50Hz/60Hz, 220 VDC, NO/NC
15A	Honeywell	DPDT Mech, AC/DC, 15A	15 Amp, 125 or 250 VAC, 60Hz/60Hz, 220 VDC, NO/NC
5B	Cherry	DPDT Mech, AC/DC, 5A	5 Amp, 125 or 250 VAC, 220 VDC, NO/NC
15B	Cherry	DPDT Mech, AC/DC, 15A	15 Amp, 125 or 250 VAC, 220 VDC, NO/NC
6A	Hermitic	Sealed Prox, AC/DC, 2A	2 Amp, 220 V ACDC, 50Hz/60Hz, NO/NC
16A	Hermitic	Sealed Prox, AC/DC, 2A	2 Amp, 220 V ACDC, 50Hz/60Hz, NO/NC

BKS1	SS 80 X 30 X 20mm
BKC1	CS 80 X 30 X 20mm
BKS2	SS 80 X 30 X 30mm
BKC2	CS 80 X 30 X 30mm
BKS3	SS 130 X 30 X 30mm
BKC3	CS 130 X 30 X 30mm
BKS4	SS 130 X 30 X 50mm
BKC4	CS 130 X 30 X 50mm

Standard Stock Items

